

# Tile-in-Series



## Tileable Surface



Pictured: Installed Tile AP TL

The **Tile-in Series Access Panel** is designed for use where access is required through a tiled surface.

### Product description

#### Material

- Constructed of 1.2mm zinc steel frame
- Composite MDF foam and PVC rot free door
- The frame is supplied without an external flange for a seamless appearance in the tile grout lines, and is supplied to accept a nominated tile thickness up to 15mm.

#### Door

- Composite MDF foam and PVC rot free door

#### Frame

- Supplied without an external flange for a seamless appearance in the tile grout lines, and is supplied to accept a nominated tile thickness up to 15mm

#### Tile recess depth

- To be nominated on order, typically tile thickness + 2mm for adhesive

#### Hinge

- Concealed cabinet hinge system to ensure the tiles do not foul against the frame when opening the door

#### Standard sizes (mm)

- 300 | 450 | 530 | 600
- Custom sizes available

#### Cut-out size

- Add 6mm to nominal size
- Refer to installation and maintenance document for more information

#### Frame depth

- 60mm | 80mm

#### Lock

- Budget lock
- Touch latch
- Key lock (need to be removed prior to tiling then reinstalled)

#### Options

- Stainless steel finish
- Flanged frame
- Setbead frame

### Product codes

(Composite MDF foam and PVC rot free door)

#### Lock type

#### Specified frame

Budget

Tile AP B (Size)

Touch latch

Tile AP TL (Size)

Key

Tile AP KL (Size)

### Lock options



Budget

Touch latch

Key lock

### Other Como Access Panels products available include:

- Acoustic Rated
- CS-Series (Metal door)
- Micro-Series
- Security Rated

Designed and manufactured in Australia

**1300 888 408**

[www.comobuildingproducts.com.au](http://www.comobuildingproducts.com.au)

Specifications subject to change without notice.